

**ISSN 2518-1726 (Online),  
ISSN 1991-346X (Print)**

ҚАЗАҚСТАН РЕСПУБЛИКАСЫ  
ҰЛТТЫҚ ҒЫЛЫМ АКАДЕМИЯСЫНЫҢ

ӘЛЬ-ФАРАБИ АТЫНДАҒЫ  
ҚАЗАҚ ҰЛТТЫҚ УНИВЕРСИТЕТИНІҢ

# Х А Б А Р Л А Р Ы

**ИЗВЕСТИЯ**

НАЦИОНАЛЬНОЙ АКАДЕМИИ НАУК  
РЕСПУБЛИКИ КАЗАХСТАН

КАЗАХСКИЙ НАЦИОНАЛЬНЫЙ  
УНИВЕРСИТЕТ ИМЕНИ АЛЬ-ФАРАБИ

**NEWS**

OF THE NATIONAL ACADEMY OF SCIENCES  
OF THE REPUBLIC OF KAZAKHSTAN

AL-FARABI KAZAKH  
NATIONAL UNIVERSITY

**ФИЗИКА-МАТЕМАТИКА СЕРИЯСЫ**

**СЕРИЯ ФИЗИКО-МАТЕМАТИЧЕСКАЯ**

**PHYSICO-MATHEMATICAL SERIES**

**2 (318)**

**НАУРЫЗ – СӘУІР 2018 ж.  
МАРТ – АПРЕЛЬ 2018 г.  
MARCH – APRIL 2018**

1963 ЖЫЛДЫҢ ҚАҢТАР АЙЫНАН ШЫҒА БАСТАҒАН  
ИЗДАЕТСЯ С ЯНВАРЯ 1963 ГОДА  
PUBLISHED SINCE JANUARY 1963

**ЖЫЛЫНА 6 РЕТ ШЫҒАДЫ  
ВЫХОДИТ 6 РАЗ В ГОД  
PUBLISHED 6 TIMES A YEAR**

**Бас редакторы**  
ф.-м.ғ.д., проф., КР ҮФА академигі **F.M. Мұтанов**

**Редакция алқасы:**

**Жұмаділдаев А.С.** проф., академик (Қазақстан)  
**Кальменов Т.Ш.** проф., академик (Қазақстан)  
**Жантаев Ж.Ш.** проф., корр.-мүшесі (Қазақстан)  
**Өмірбаев Ү.Ү.** проф. корр.-мүшесі (Қазақстан)  
**Жусіпов М.А.** проф. (Қазақстан)  
**Жұмабаев Д.С.** проф. (Қазақстан)  
**Асанова А.Т.** проф. (Қазақстан)  
**Бошкаев К.А.** PhD докторы (Қазақстан)  
**Сұраған Ә.** корр.-мүшесі (Қазақстан)  
**Quevedo Hernando** проф. (Мексика),  
**Джунушалиев В.Д.** проф. (Қыргызстан)  
**Вишневский И.Н.** проф., академик (Украина)  
**Ковалев А.М.** проф., академик (Украина)  
**Михалевич А.А.** проф., академик (Белорус)  
**Пашаев А.** проф., академик (Әзірбайжан)  
**Такибаев Н.Ж.** проф., академик (Қазақстан), бас ред. орынбасары  
**Тигиняну И.** проф., академик (Молдова)

**«КР ҮФА Хабарлары. Физика-математикалық сериясы».**

**ISSN 2518-1726 (Online), ISSN 1991-346X (Print)**

Меншіктенуші: «Қазақстан Республикасының Үлттық ғылым академиясы» РКБ (Алматы қ.)  
Қазақстан республикасының Мәдениет пен ақпарат министрлігінің Ақпарат және мұрағат комитетінде  
01.06.2006 ж. берілген №5543-Ж мерзімдік басылым тіркеуіне қойылу туралы қуәлік

Мерзімділігі: жылдана 6 рет.

Тиражы: 300 дана.

Редакцияның мекенжайы: 050010, Алматы қ., Шевченко көш., 28, 219 бөл., 220, тел.: 272-13-19, 272-13-18,  
[www.nauka-nanrk.kz](http://www.nauka-nanrk.kz) / [physics-mathematics.kz](http://physics-mathematics.kz)

---

© Қазақстан Республикасының Үлттық ғылым академиясы, 2018

Типографияның мекенжайы: «Аруна» ЖК, Алматы қ., Муратбаева көш., 75.

Г л а в н ы й р е д а к т о р  
д.ф.-м.н., проф. академик НАН РК **Г.М. Мутанов**

Р е д а к ц и о н на я кол л е г и я:

**Джумадильдаев А.С.** проф., академик (Казахстан)  
**Кальменов Т.Ш.** проф., академик (Казахстан)  
**Жантаев Ж.Ш.** проф., чл.-корр. (Казахстан)  
**Умирбаев У.У.** проф. чл.-корр. (Казахстан)  
**Жусупов М.А.** проф. (Казахстан)  
**Джумабаев Д.С.** проф. (Казахстан)  
**Асанова А.Т.** проф. (Казахстан)  
**Бошкаев К.А.** доктор PhD (Казахстан)  
**Сураган Д.** чл.-корр. (Казахстан)  
**Quevedo Hernando** проф. (Мексика),  
**Джунушалиев В.Д.** проф. (Кыргызстан)  
**Вишневский И.Н.** проф., академик (Украина)  
**Ковалев А.М.** проф., академик (Украина)  
**Михалевич А.А.** проф., академик (Беларусь)  
**Пашаев А.** проф., академик (Азербайджан)  
**Такибаев Н.Ж.** проф., академик (Казахстан), зам. гл. ред.  
**Тигиняну И.** проф., академик (Молдова)

«Известия НАН РК. Серия физико-математическая».

**ISSN 2518-1726 (Online), ISSN 1991-346X (Print)**

Собственник: РОО «Национальная академия наук Республики Казахстан» (г. Алматы)

Свидетельство о постановке на учет периодического печатного издания в Комитете информации и архивов Министерства культуры и информации Республики Казахстан №5543-Ж, выданное 01.06.2006 г.

Периодичность: 6 раз в год.

Тираж: 300 экземпляров.

Адрес редакции: 050010, г. Алматы, ул. Шевченко, 28, ком. 219, 220, тел.: 272-13-19, 272-13-18,  
[www.nauka-nanrk.kz](http://www.nauka-nanrk.kz) / [physics-mathematics.kz](http://physics-mathematics.kz)

---

© Национальная академия наук Республики Казахстан, 2018

Адрес типографии: ИП «Аруна», г. Алматы, ул. Муратбаева, 75.

**E d i t o r i n c h i e f**  
doctor of physics and mathematics, professor, academician of NAS RK **G.M. Mutanov**

E d i t o r i a l b o a r d:

**Dzhumadildayev A.S.** prof., academician (Kazakhstan)  
**Kalmenov T.Sh.** prof., academician (Kazakhstan)  
**Zhantayev Zh.Sh.** prof., corr. member. (Kazakhstan)  
**Umirbayev U.U.** prof. corr. member. (Kazakhstan)  
**Zhusupov M.A.** prof. (Kazakhstan)  
**Dzhumabayev D.S.** prof. (Kazakhstan)  
**Asanova A.T.** prof. (Kazakhstan)  
**Boshkayev K.A.** PhD (Kazakhstan)  
**Suragan D.** corr. member. (Kazakhstan)  
**Quevedo Hernando** prof. (Mexico),  
**Dzhunushaliyev V.D.** prof. (Kyrgyzstan)  
**Vishnevskyi I.N.** prof., academician (Ukraine)  
**Kovalev A.M.** prof., academician (Ukraine)  
**Mikhalevich A.A.** prof., academician (Belarus)  
**Pashayev A.** prof., academician (Azerbaijan)  
**Takibayev N.Zh.** prof., academician (Kazakhstan), deputy editor in chief.  
**Tiginyanu I.** prof., academician (Moldova)

**News of the National Academy of Sciences of the Republic of Kazakhstan. Physical-mathematical series.**

**ISSN 2518-1726 (Online), ISSN 1991-346X (Print)**

Owner: RPA "National Academy of Sciences of the Republic of Kazakhstan" (Almaty)

The certificate of registration of a periodic printed publication in the Committee of information and archives of the Ministry of culture and information of the Republic of Kazakhstan N 5543-Ж, issued 01.06.2006

Periodicity: 6 times a year

Circulation: 300 copies

Editorial address: 28, Shevchenko str., of. 219, 220, Almaty, 050010, tel. 272-13-19, 272-13-18,  
[www.nauka-nanrk.kz](http://www.nauka-nanrk.kz) / [physics-mathematics.kz](http://physics-mathematics.kz)

---

© National Academy of Sciences of the Republic of Kazakhstan, 2018

Address of printing house: ST "Aruna", 75, Muratbayev str, Almaty

**NEWS**

OF THE NATIONAL ACADEMY OF SCIENCES OF THE REPUBLIC OF KAZAKHSTAN

**PHYSICO-MATHEMATICAL SERIES**

ISSN 1991-346X

Volume 2, Number 318 (2018), 21 – 30

УДК 539.3

MSQ 74J15

**L.A. Alexeyeva**

Institute of mathematics and mathematical modelling , Almaty, Kazakhstan  
 alexeeva@math.kz

## **BOUNDARY VALUE PROBLEM FOR ELASTIC HALF-SPACE BY SUBSONIC VELOCITIES OF SURFACE TRANSPORT LOADS MOVING**

**Abstract.** The first boundary value problem of the theory of elasticity for an elastic half-space at the movement on its surface of subsonic trans loads is considered. The speed of motion is less or more than the speed of distribution of elastic Rayleigh waves. On the basis of the generalized Fourier's transformation the fundamental solution of a task is constructed which describes dynamics of the massif at the movement of the concentrated force on and along its surface. Based on this, an analytical solution is constructed for arbitrary transport loads distributed over the surface, moving with the pre-Rayleigh and super-Rayleigh velocities. It is shown that when the Rayleigh wave velocity is exceeded, the transport loads generate surface Rayleigh waves.

The task is a model for research of the intense deformed condition of the pedigree massif in the vicinity of road constructions at moving transport.

**Keywords:** boundary value problem, an elastic half-space, trans loading, subsonic speed, Rayleigh wave, the stress-strain state.

Trans loads are very widespread in practice. As those we understand the moving loads which form doesn't change over time, but their position are changing in the environment. Dynamic deformation processes, which arise in the ground under their influence, expand with different speeds, characterizing elastic properties of the medium. In isotropic elastic medium there are two sound speeds of expansion of *dilatation waves* ( $c_1$ ) and *shift (c<sub>2</sub>) waves* ( $c_1 > c_2$ ). The relation of speed of trans load to the sound velocities significantly influences to the stresses and deformations in the elastic medium. We consider here the subsonic case, when speeds of loads are less then shift waves speed. This case is characteristic for trans problems as the speed of the movement of the most modern vehicles is many less then the speeds of elastic waves propagation. From trans loads we especially distinguish stationary ones which move in the fixed direction with a constant speed (*transport loads*). This class of loads allows to investigate diffraction processes in isotropic elastic medium in analytical form.

In papers [1-3] the fundamental and generalized solutions of the Lame's equations are constructed and investigated which describe the movement of elastic medium at the action of concentrated on an axis and distributed loading in all range of speeds (subsonic, sound, transonic and supersonic ones). On this basis in [4-7] the method of boundary integral equations has been developed for solving the transport BVP in elastic medium with cylindrical boundaries. This class of problems is very important for applications in the field of dynamics of underground constructions, trans tunnels and excavations of deep laying.

However there is a class of model trans tasks (for example, road problems) when loadings move on the surface of a half-space. It is known that there is also sound speed in an elastic half-space with which superficial Rayleigh waves are propagating. The Rayleigh's speed is less, but is very close to the speed of shift waves [10,11]. Rayleigh's waves don't create tensions on half-space border, but significantly influence on the tensions and deformations of the massif near a free surface.

For the first time such task was considered and solved for a subsonic pre-Rayleigh case by flat deformation in work [8]. Here the analytical solution of this task in three-dimensional statement is

constructed also in a subsonic case, when the speed of subsonic trans load is less or more than the Rayleigh's speed.

### 1. The statement of transport boundary value problem for elastic half-space

Elastic isotropic medium, with Lame's parameters  $\lambda, \mu$  and the density  $\rho$ , occupies half-plane  $x_1 > 0$ ,  $\mathbf{n}(x) = (-1, 0, 0)$  is unit vector of the external normal to its boundary  $D = \{x \in R^3 : x_1 = 0\}$ . Constants  $c_1$  and  $c_2$  are the velocities of elastic waves propagation [11]:

$$c_1 = \sqrt{\frac{\lambda + 2\mu}{\rho}}, \quad c_2 = \sqrt{\frac{\mu}{\rho}}, \quad c_2 < c_1 \text{ (sonic speeds):}$$

Boundary transport load  $\mathbf{P}(x, t)$  are moving with constant subsonic speed ( $c < c_2 < c_1$ ) along the axis  $X_3$ :  $\mathbf{P}(x, t) = \mu p_j(x_2, x_3 + ct) e_j$ . Components of stress tensor  $\sigma_{ij}$  are connected with medium displacements  $u(x, t)$  by Hook's law:

$$\sigma_{ij} = \lambda \operatorname{div} u \delta_{ij} + \mu (u_{i,j} + u_{j,i}).$$

For dynamics problems this law better to write in the unitless form:

*Hook's law:*

$$\frac{\sigma_{ij}}{\mu} = \left( \frac{c_1^2}{c_2^2} - 2 \right) \operatorname{div} u \delta_{ij} + (u_{i,j} + u_{j,i}) \quad (1)$$

Here and everywhere further on the identical indexes the tensor convolution have been made. Private derivatives on the corresponding coordinate are designated by the index after comma:  $u_{i,j} = \frac{\partial u_i}{\partial x_j}$ ;

$\delta_{ij} = \delta_i^j$  is Kronecker symbol.

The stationary movement has been considered that allows to pass into mobile coordinates system which are connected with transport load. Further we use designations:  $x = (x_1, x_2)$ ,  $z = x_3 + ct$ .

It's supposed that components of the load allow the Fourier's transformation, i.e. they are representable in the form of Fourier's integrals:

$$\begin{aligned} P_j(x_2, z) &= \sigma_{j1}(0, x_2, z) = \frac{\mu}{(2\pi)^2} \int_{R^2} \bar{p}_n(\eta, \zeta) \exp(-i(x_2\eta + \zeta z)) d\eta d\zeta \\ \bar{p}_n(\eta, \zeta) &= \int_{R^2} p_n(x_2, z) \exp(i(x_2\eta + z\zeta)) dx_2 dz \end{aligned} \quad (2)$$

The Lame's equations for displacements of elastic half-space in mobile coordinates system have the form [1]:

$$\left( (M_1^{-2} - M_2^{-2}) \frac{\partial^2}{\partial x_i \partial x_j} + (M_2^{-2} \Delta - (\partial_z)^2) \delta_i^j \right) u_j = 0 \quad (3)$$

This operator we denote  $L_{ij}$  ( $\partial_1, \partial_2, \partial_z$ ). Here two Mach's numbers are introduced:

$$M_1 = c / c_1, \quad M_2 = c / c_2,$$

which characterize the velocity of transport load in relation to the sound speeds of elastic waves.

Eqs. (3) were studied in [2,3]. There are three cases: subsonic ( $c < c_2$ ), transonic ( $c_2 < c < c_1$ ), supersonic ( $c > c_1$ ) and two sonic cases ( $c = c_2, c = c_1$ ). In the first case ( $M_1 < 1, M_2 < 1$ ) the system (3) is elliptic, in the second one ( $M_1 < 1, M_2 > 1$ ) it has have the mixed elliptic-hyperbolic type. In

supersonic case ( $M_1 > 1, M_2 > 1$ ) this system is strong hyperbolic. By sonic speeds it is mixed parabolic-elliptic if  $M_1 < 1, M_2 = 1$ , and it's hyperbolic-parabolic if  $M_1 = 1, M_2 > 1$ .

By sonic and supersonic velocities the shock waves can appear in elastic medium. There are the next conditions on the jumps on their fronts  $F$ :

$$\begin{aligned} [u_j]_F = 0 \quad \Rightarrow \quad h_z [u_{i,j}]_F = h_j [u_{i,z}]_F; \\ h_j [\sigma_{ij}]_F = \rho c^2 h_z [u_{i,z}]_F, \quad i, j = 1, 2, 3. \end{aligned} \quad (4)$$

Here  $h(x_1, x_2, z) = (h_1, h_2, h_3 \square h_z)$  is wave vector,  $\|h\| = 1$ . It's perpendicular to a front  $F$  in the direction of wave propagation. The continuity of elastic medium gives the first condition. The second condition is continuity of tangent derivatives at the front of a wave; it is consequence from the first one. The third formula is law of momentum conservation on waves fronts.

Here we consider the subsonic case. It's required to find the solution of the BVP which must to satisfy

*the attenuation condition on infinity:*

$$u \rightarrow 0 \quad \text{by} \quad x_1 \rightarrow +\infty \quad \text{or} \quad z \rightarrow \pm\infty. \quad (5)$$

Also we'll enter later some additional *radiation conditions* by construction of BVP solution.

## 1. Green tensor of transport BVP

To solve the problem, we construct the Green's tensor  $\Pi_j^k$  of the boundary value problem in a moving coordinates system. For its determination we have the following boundary value problem.

To find the tensor solution of homogeneous motion equations :

$$\left( (M_1^{-2} - M_2^{-2}) \frac{\partial^2}{\partial x_i \partial x_j} + \left( M_2^{-2} \Delta - \frac{\partial^2}{\partial z^2} \right) \delta_i^j \right) \Pi_j^k = 0, \quad i, j, k = 1, 2, 3, \quad (6)$$

in the region  $x_1 > 0$ , which must to satisfy the attenuation condition at infinity:

$$\Pi_j^k(x, z) \rightarrow 0 \quad \text{for} \quad \|(x, z)\| \rightarrow 0. \quad (7)$$

Corresponding stress tensor  $\Sigma_{jk}^m$ , which are calculated by use Hooke's law (2), has the form:

$$\begin{aligned} \Sigma_{jk}^m = \alpha \Pi_{l,l}^m \delta_{jk} + (\Pi_{j,k}^m + \Pi_{k,j}^m) = S_{jk}^l (\partial_1, \partial_2, \partial_z) \Pi_l^m(x_1, x_2, z), \\ S_{jk}^l = \alpha \delta_{jk} \partial_l + (\delta_{jl} \partial_k + \delta_{lk} \partial_j) \end{aligned} \quad (8)$$

**Theorem.** *The solution of the given boundary-value problem has the form of the following convolution on the boundary of a half-space*

$$u_j(x_1, x_2, z) = \int_{R^q}^{\infty} \Pi_j^n(x_1, x_2 - y_2, z - y_3) p_n(y_2, y_3) dy_2 dy_3, \quad j = 1, 2, 3. \quad (9)$$

and must satisfy to the following singular conditions on the free surface : for  $x_1=0$

$$\Sigma_{i1}^m = \alpha \Pi_{k,k}^m \delta_{i1} + (\Pi_{i,1}^m + \Pi_{1,i}^m) = \delta_i^m \delta(x_2) \delta(z), \quad i, m, k = 1, 2, 3. \quad (10)$$

where  $\delta(x_j)$  is generalized Dirac function,  $\alpha = \frac{\lambda}{\mu} = \left( \frac{c_1^2}{c_2^2} - 2 \right) = \left( \frac{M_2^2}{M_1^2} - 2 \right)$ .

**P r o o f.** Indeed, by virtue of (1), (10) and the convolution properties we have on the boundary of the half-space:

$$\int\limits_{R^q}^{\infty} \Sigma_{j1}^m(0, x_2 - y_2, z - y_3) p_m(y_2, y_3) dy_2 dy_3 = \delta_j^m \delta(x_2) \delta(z) * p_m(x_2, z) = p_j(x_2, z).$$

Here on the right there is a functional convolution along the half-space boundary and tensor convolution by the index  $m$ . The displacements (9) satisfy to the homogeneous transport Lame equations (3) in the half-space:

$$L_i^j(\partial_1, \partial_2, \partial_z) u_j = \int\limits_{R^q}^{\infty} p_n(y_2, y_3) L_i^j(\partial_1, \partial_2, \partial_z) \Pi_j^n(x_1, x_2 - y_2, z - y_3) dy_2 dy_3 = 0$$

in view of (6) and the invariance of these equations with respect to the shift at the boundary of the half-space

This tensor  $\Pi(x, z)$  gives possibility to use the formula (9) for determination of displacements in a half-space for any loading on its surface. The stresses at any point of the elastic half-space on the area with the normal  $n$  are determined by the formula

$$\begin{aligned} S(x_1, x_2, z, n) &= \sigma_{jk}(x_1, x_2, z) n_j e_k = \\ &= \mu e_k n_j \int\limits_{R^q}^{\infty} \Sigma_{kj}^l(x_1, x_2 - y_2, z - y_3) p_l(y_2, y_3) dy_2 dy_3. \end{aligned} \quad (11)$$

Thus, the definition of the fundamental displacement tensor determines the solution of the problem. We construct the tensor  $\Pi(x, z)$  using the scalar and vector elastic Lame potentials.

## 2. Statement of the transport problem for Lame's potentials

The displacements of the elastic medium can be represented in terms of the scalar and vector Lame's potentials [1,11]:

$$u = \text{grad} \varphi + \text{rot} \psi \quad (12)$$

Since the three components of the displacements are determined through four potential components, the vector potential is usually associated with a Gaussian or Lorentz gauge. Here it is convenient to use the representation:

$$\psi = \psi_1 e_3 + \text{rot}(\psi_2 e_3),$$

which uniquely links the three components of displacements with three potentials. If the displacements satisfy to the homogeneous Lame equations, then the potentials satisfy the d'Alembert's wave equation with the corresponding velocity:

$$\begin{aligned} c_1^2 \Delta \varphi - \frac{\partial^2 \varphi}{\partial t^2} &= 0, \\ c_2^2 \Delta \psi_k - \frac{\partial^2 \psi_k}{\partial t^2} &= 0, \quad k = 1, 2 \end{aligned} \quad (12)$$

where  $\Delta$  is Laplace operator. In the moving coordinate system these equations are transformed to the form:

$$\begin{aligned} \Delta \varphi - M_1^2 \frac{\partial^2 \varphi}{\partial z^2} &= 0, \\ \Delta \psi_k - M_2^2 \frac{\partial^2 \psi_k}{\partial z^2} &= 0, \quad k = 1, 2 \end{aligned} \quad (13)$$

To construct the tensor  $\Pi_j^i$ , we use similar potentials. Namely, we represent it in the form

$$\begin{aligned}\Pi_k^m(x_1, x_2, z) &= D_{kn}(\partial_1, \partial_2, \partial_z)\Phi_n^m = \partial_k\Phi_1^m + e_{ki3}\partial_i\Phi_2^m + e_{kjl}e_{li3}\partial_j\partial_i\Phi_3^m \\ D_{k1}(\partial_1, \partial_2, \partial_z) &= \partial_k \\ D_{k2}(\partial_1, \partial_2, \partial_z) &= e_{ki3}\partial_i \\ D_{k3}(\partial_1, \partial_2, \partial_z) &= e_{kjl}e_{li3}\partial_j\partial_i\end{aligned}\tag{14}$$

Here  $i,j,k,l,m=1,2,3$ ,  $e_{ijk}$  is Levi-Civita pseudotensor. The first potential describes the gradient component of the displacements field, and the other two potentials describe the rotor (solenoidal) components. The potentials satisfy to the

*transport wave equations:*

$$\Delta\Phi_j^m - M_j^2 \frac{\partial^2\Phi_j^m}{\partial z^2} = 0, \quad j=1,2,3.\tag{15}$$

We name them *fundamental potentials*. To calculate them we use boundary conditions (9) :

by  $x_1 = 0$

$$\alpha\Pi_k^m, k + (\Pi_i^m, _1 + \Pi_i^m, _i) = \delta_i^m\delta(x_2)\delta(z)$$

where

$$\begin{aligned}\Pi_k^m, k &= \Delta\Phi_1^m + e_{ki3}\partial_k\partial_i\Phi_2^m + e_{kjl}e_{li3}\partial_k\partial_i\partial_j\Phi_3^m, \\ \Pi_i^m, _1 &= \partial_i\partial_1\Phi_1^m + e_{ik3}\partial_k\partial_1\Phi_2^m + e_{ijl}e_{lk3}\partial_k\partial_j\partial_1\Phi_3^m, \\ \Pi_i^m, _i &= \partial_i\partial_1\Phi_1^m + e_{1k3}\partial_k\partial_i\Phi_2^m + e_{1jl}e_{lk3}\partial_k\partial_j\partial_i\Phi_3^m,\end{aligned}$$

We can to write it in the form:

$$B_{in}(\partial_1, \partial_2, \partial_z)\Phi_n^m = \delta_i^m\delta(x_2)\delta(z), \quad n, m = 1, 2, 3,\tag{16}$$

where

$$\begin{aligned}B_{in}\Phi_n^m &= [2\partial_i\partial_1\Phi_1^m + \partial_k\{(e_{ik3}\partial_1 + e_{1k3}\partial_i)\Phi_2^m + \partial_j(e_{ijl}e_{lk3}\partial_1 + e_{1jl}e_{lk3}\partial_i)\Phi_3^m\}] + \\ &\quad + \alpha[\Delta\Phi_1^m + e_{kjl}\partial_k\partial_j\Phi_2^m + e_{kjl}e_{ls3}\partial_k\partial_s\partial_j\Phi_3^m]\delta_{i1} \Rightarrow \\ B_{in}(\partial_1, \partial_2, \partial_z)\Phi_n^m &= (\alpha\delta_{i1}\Delta + 2\partial_1\partial_i)\Phi_1^m + \partial_k(\alpha\delta_{i1}e_{kj3}\partial_j + e_{ik3}\partial_1 + e_{1k3}\partial_i)\Phi_2^m + \\ &\quad + \partial_k\partial_j\{\alpha\delta_{i1}e_{kjl}e_{ls3}\partial_s + (e_{ijl}e_{lk3}\partial_1 + e_{1jl}e_{lk3}\partial_i)\}\Phi_3^m = \\ &= (\alpha M_1^2\delta_{i1}\partial_z\partial_z + 2\partial_1\partial_i)\Phi_1^m + \partial_k(\alpha\delta_{i1}e_{kj3}\partial_j + e_{ik3}\partial_1 + e_{1k3}\partial_i)\Phi_2^m + \\ &\quad + \partial_k\partial_j\{\alpha\delta_{i1}e_{kjl}e_{ls3}\partial_s + (e_{ijl}e_{lk3}\partial_1 + e_{1jl}e_{lk3}\partial_i)\}\Phi_3^m\end{aligned}$$

This implies

$$\begin{aligned}B_{i1}(\partial_1, \partial_2, \partial_z) &= (\alpha M_1^2\delta_{i1}\partial_z\partial_z + 2\partial_1\partial_i), \\ B_{i2}(\partial_1, \partial_2, \partial_z) &= \partial_k(\alpha\delta_{i1}e_{kj3}\partial_j + e_{ik3}\partial_1 + e_{1k3}\partial_i), \\ B_{i3}(\partial_1, \partial_2, \partial_z) &= \partial_k\partial_j\{\alpha\delta_{i1}e_{kjl}e_{ls3}\partial_s + (e_{ijl}e_{lk3}\partial_1 + e_{1jl}e_{lk3}\partial_i)\}\end{aligned}$$

Using the properties of the permutation of the indices of the Levi-Civita tensor and the formula for its convolution:

$$e_{lij}e_{lkm} = \delta_{ik}\delta_{jm} - \delta_{im}\delta_{kj},$$

these operators can be greatly simplified:

$$\begin{aligned}
 B_{11}(\partial_1, \partial_2, \partial_z) &= (\alpha M_1^2 \partial_z^2 + 2\partial_1^2), \\
 B_{21}(\partial_1, \partial_2, \partial_z) &= 2\partial_1 \partial_2, \quad B_{31}(\partial_1, \partial_2, \partial_z) = 2\partial_1 \partial_3, \\
 B_{12}(\partial_1, \partial_2, \partial_z) &= \partial_k (\alpha e_{kj3} \partial_j + e_{lk3} \partial_1 + e_{lk3} \partial_1) = (\alpha e_{kj3} \partial_k \partial_j + 2\partial_1 \partial_2) = \\
 &= \alpha (e_{123} \partial_1 \partial_2 + e_{213} \partial_2 \partial_1) + 2\partial_1 \partial_2 = 2\partial_1 \partial_2, \\
 B_{22}(\partial_1, \partial_2, \partial_z) &= \partial_k (\alpha \delta_{21} e_{kj3} \partial_j + e_{2k3} \partial_1 + e_{lk3} \partial_2) = \\
 &= (e_{213} \partial_1 \partial_1 + e_{123} \partial_2 \partial_2) = \partial_2 \partial_2 - \partial_1 \partial_1, \\
 B_{32}(\partial_1, \partial_2, \partial_z) &= \partial_k (e_{3k3} \partial_1 + e_{lk3} \partial_3) = \partial_2 \partial_3, \\
 B_{13}(\partial_1, \partial_2, \partial_z) &= \partial_k \partial_j \left\{ \alpha e_{kjl} e_{lm3} \partial_m + (e_{1jl} e_{lk3} \partial_1 + e_{1jl} e_{lk3} \partial_1) \right\} = \\
 &= \alpha (\delta_{km} \delta_{j3} - \delta_{kj} \delta_{m3}) \partial_k \partial_j \partial_m + (\delta_{1k} \delta_{j3} - \delta_{13} \delta_{jk}) \partial_1 \partial_k \partial_j + \\
 &+ (\delta_{1k} \delta_{j3} - \delta_{13} \delta_{jk}) \partial_1 \partial_k \partial_j = \alpha (\delta_3 \partial_m \partial_m - \partial_3 \partial_j \partial_j) + 2\partial_1 \partial_1 \partial_3 = 2\partial_1 \partial_1 \partial_3, \\
 B_{23}(\partial_1, \partial_2, \partial_z) &= e_{2jl} e_{lk3} \partial_1 \partial_k \partial_j + e_{1jl} e_{lk3} \partial_2 \partial_k \partial_j = \\
 &= (\delta_{2k} \delta_{j3} - \delta_{23} \delta_{jk}) \partial_1 \partial_k \partial_j + (\delta_{1k} \delta_{j3} - \delta_{13} \delta_{jk}) \partial_2 \partial_k \partial_j = 2\partial_1 \partial_2 \partial_3, \\
 B_{33}(\partial_1, \partial_2, \partial_z) &= e_{2jl} e_{lk3} \partial_1 \partial_k \partial_j + e_{1jl} e_{lk3} \partial_2 \partial_k \partial_j = \\
 &= (\delta_{2k} \delta_{j3} - \delta_{23} \delta_{jk}) \partial_1 \partial_k \partial_j + (\delta_{1k} \delta_{j3} - \delta_{13} \delta_{jk}) \partial_2 \partial_k \partial_j = 2\partial_1 \partial_2 \partial_3.
 \end{aligned}$$

As a result, we get:

$$\begin{aligned}
 B_{11} &= (\alpha M_1^2 \partial_z \partial_z + 2\partial_1^2), \quad B_{12} = 2\partial_1 \partial_2, \quad B_{13} = 2\partial_1^2 \partial_3, \\
 B_{21}(\partial_1, \partial_2, \partial_z) &= 2\partial_1 \partial_2, \quad B_{22}(\partial_1, \partial_2, \partial_z) = \partial_2 \partial_2 - \partial_1 \partial_1, \quad B_{23}(\partial_1, \partial_2, \partial_z) = 2\partial_1 \partial_2 \partial_3, \quad (17) \\
 B_{31}(\partial_1, \partial_2, \partial_z) &= 2\partial_1 \partial_3, \quad B_{32}(\partial_1, \partial_2, \partial_z) = 2\partial_2 \partial_3, \quad B_{33}(\partial_1, \partial_2, \partial_z) = 2\partial_1 \partial_2 \partial_3.
 \end{aligned}$$

Thus, the problem of constructing the transformants of the unknown tensors reduces to determining the Lamé potentials satisfying equations (14), the boundary conditions on the free surface (16), and the damping conditions at infinity:

$$\Phi_j^k \rightarrow 0 \text{ by } \|(x, z)\| \rightarrow \infty, \quad (18)$$

and certain radiation conditions, which we discuss below.

### 3. Determination of Fourier transforms of fundamental potentials

To construct the solution, we use the Fourier transform of the potentials with respect to  $x_2, z$ . In the space of Fourier transforms, they correspond to variables  $\eta, \zeta$ . Their Fourier transforms are defined by the relations:

$$\bar{\Phi}^m = \int_{R^2} \Phi^m(x, z) \exp(i\eta x_2 + i\zeta z) dz dx_2, \quad \Phi^m = \frac{1}{4\pi^2} \int_{R^2} \bar{\Phi}^m(x, \eta, \zeta) \exp(-i\eta x_2 - i\zeta z) d\zeta d\eta$$

In the space of Fourier transforms the equations for the potentials (14) have the form:

$$\frac{d^2 \bar{\Phi}_j^m}{dx_1^2} - \eta^2 \bar{\Phi}_j^m - \alpha_j^2 \zeta^2 \bar{\Phi}_j^m = 0, \quad \alpha_j = \sqrt{1 - M_j^2}, \quad j = 1, 2, 3. \quad (19)$$

The expression under radical is positive, because we consider the subsonic case. The boundary conditions are transformed to the form:

$$B_{ik}(\partial_1, -i\eta, -i\zeta)\bar{\Phi}_k^m(x_1, \eta, \zeta) = \delta_i^m \text{ by } x_1 = 0. \quad (20)$$

Conditions for damping at infinity: for  $\forall \eta, \zeta$

$$\bar{\Phi}_k^m(x_1, \eta, \zeta) \rightarrow 0 \text{ by } x_1 \rightarrow \infty. \quad (21)$$

By these conditions the solution of Eq. (19) has the form:

$$\bar{\Phi}_j^k = \varphi_j^k(\eta, \zeta) \exp\left(-x_1 \sqrt{\eta^2 + \alpha_j^2 \zeta^2}\right), \text{ Re} \sqrt{\eta^2 + \alpha_j^2 \zeta^2} \geq 0. \quad (22)$$

Functions  $\varphi_j^k(\eta, \zeta)$  are determined from boundary conditions (19):

$$\sum_{j=1}^3 B_{in}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, -i\eta, -i\zeta) \varphi_j^m = \delta_i^m, \quad k=1,2,3 \quad (23)$$

Thus, for each fixed  $m$ , we have the linear system of three equations for determination  $\varphi_k^m$ , from which we find

$$\varphi_j^m = \frac{\Delta_j^m(\eta, \zeta)}{\Delta(\eta, \zeta)}. \quad (24)$$

Here  $\Delta_j^m$  is corresponding algebraic complement, and the denominator is equal to

$$\Delta(\eta, \zeta) = \det\{B_{kj}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, -i\eta, -i\zeta)\}.$$

This is a well-known Rayleigh determinant. In this case it has the form:

$$\Delta = 4\nu^2 \sqrt{\nu^2 - M_1^2 \zeta^2} \sqrt{\nu^2 - M_2^2 \zeta^2} - (2\nu^2 - M_2^2 \zeta^2)^2, \quad \nu^2 = \zeta^2 + \eta^2. \quad (25)$$

The properties of Rayleigh determinant are known. For transport problems, it was well studied in [1]. In particular,

$$\begin{aligned} \Delta(\eta, \zeta) &= 0 \\ \text{by } \eta = \eta_R^\pm(\zeta) = \pm |\zeta| \sqrt{M_R^2 - 1} &\Leftrightarrow \zeta = \zeta_R^\pm(\eta) = \pm \frac{|\eta|}{\sqrt{M_R^2 - 1}} \end{aligned} \quad (26)$$

where  $M_R = c/c_R$ ,  $c_R$  is the velocity of the surface Rayleigh wave, which is subsonic ( $c_R < c_2$ ). It can be determined from the equation:

$$4\sqrt{1 - m_1^2} \sqrt{1 - m_2^2} - (2 - m_2^2)^2 = 0, \quad m_j = c_R / c_j \quad (27)$$

Formulae (22), (24) formally resolve the problem in the potentials. However, in order to reconstruct the originals, it is necessary to investigate the properties of the transformants - integrand functions in (18), which essentially depend on the speed of a transport load.

## 6. Restoration of originals $\Pi_k^m$ and $\Sigma_{jk}^m$ by pre-Rayleigh speed $c$

From (14) we get

$$\begin{aligned} \bar{\Pi}_k^m &= D_{kn}(\partial_1, -i\eta, -i\zeta) \bar{\Phi}_n^m(x_1, \eta, \zeta) = \frac{\Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} D_{kn}(\partial_1, -i\eta, -i\zeta) \exp\left(-x_1 \sqrt{\eta^2 + \alpha_n \zeta^2}\right) \Rightarrow \\ \bar{\Pi}_k^m &= \frac{\Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} D_{kn}(-\sqrt{\eta^2 + \alpha_n \zeta^2}, -i\eta, -i\zeta) \exp\left(-x_1 \sqrt{\eta^2 + \alpha_n \zeta^2}\right) \end{aligned} \quad (28)$$

$$\bar{\Pi}_k^m(x_1, \eta, \zeta) = D_{kn}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, -i\eta, -i\zeta) \varphi_n^m(x_1, \eta, \zeta) \exp(-x_1 \sqrt{\eta^2 + \alpha_n^2 \zeta^2}) \quad (28)$$

Using the inverse Fourier transform, we obtain

$$\begin{aligned} \Pi_k^m(x_1, x_2, z) &= (2\pi)^{-2} \int_{R^2} \bar{\Pi}_k^m(x_1, \eta, \zeta) \exp(-i(\eta x_2 + \zeta z)) d\zeta d\eta = \\ &= (2\pi)^{-2} \int_{R^2} D_{kn}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, i\eta, i\zeta) \varphi_n^m(\eta, \zeta) \exp(-x_1 \sqrt{\eta^2 + \alpha_j^2 \zeta^2} - i\eta x_2 - i\zeta z) d\zeta d\eta = \quad (29) \\ &= (2\pi)^{-2} \int_{R^2} \frac{D_{kn}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, i\eta, i\zeta) \Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} \exp(-x_1 \sqrt{\eta^2 + \alpha_j^2 \zeta^2} - i\eta x_2 - i\zeta z) d\zeta d\eta \end{aligned}$$

Let us calculate the fundamental stresses and their transformants. For this, we use the formulas (10), from which we obtain

$$\begin{aligned} \Sigma_{jk}^m &= \lambda \Pi_l^m \delta_{jk} + \mu (\Pi_j^m \delta_{jk} + \Pi_k^m \delta_{kj}) = S_{jk}^l (\partial_1, \partial_2, \partial_z) \Pi_l^m = \\ &= S_{jk}^l (\partial_1, \partial_2, \partial_z) D_{ln} (\partial_1, \partial_2, \partial_z) \Phi_n^m(x_1, x_2, z) = T_{jkn} (\partial_1, \partial_2, \partial_z) \Phi_n^m(x_1, x_2, z), \quad (30) \\ T_{jkn} &= S_{jk}^l (\partial_1, \partial_2, \partial_z) D_{ln} (\partial_1, \partial_2, \partial_z) \end{aligned}$$

Hence we get

$$\begin{aligned} \bar{\Sigma}_{jk}^m &= T_{jkn} (-\sqrt{\eta^2 + \alpha_n^2 \zeta^2}, -i\eta, -i\zeta) \hat{\Phi}_n^m(x_1, \eta, \zeta) = \\ &= T_{jkn} (-\sqrt{\eta^2 + \alpha_n^2 \zeta^2}, -i\eta, -i\zeta) \frac{\Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} \exp\left(-x_1 \sqrt{\eta^2 + \alpha_n^2 \zeta^2}\right) \end{aligned}$$

The original of the stress tensor in any point  $(x, z)$  is calculated by use the formula

$$\Sigma_{jk}^m(x_1, x_2, z) = (2\pi)^{-2} \int_{R^2} \bar{\Sigma}_{jk}^m(x_1, \eta, \zeta) \exp(-i(\eta x_2 + \zeta z)) d\zeta d\eta. \quad (31)$$

For  $c < c_R$  the determinant  $\Delta(\eta, \zeta) \neq 0$  for any real  $\zeta, \eta$ . That is, at the pre-Rayleigh velocities all the integrands are continuous and tend exponentially to zero when  $(\eta, \zeta)$  tends to infinity. Therefore, the integrals exist and satisfy the damping conditions at infinity.

When  $x_1 = 0, (x_2, z) \neq (0, 0)$ , the integrands in (29) and (31) are also continuous and integrable, since they are oscillating and have the order of damping not lower  $O((\eta^2 + \zeta^2)^{-1})$ .

## 7. Determination of displacements and stresses at pre-Rayleigh speeds of transport load

To calculate the displacements of the medium for arbitrary transport load, we find the Fourier transform of the displacements. According to (9) and the convolution properties

$$\bar{u}_j(x_1, \eta, \zeta) = F_{x_2, z}[u_j(x_1, x_2, z)] = \bar{\Pi}_j^n(x_1, \eta, \zeta) \bar{p}_n(\eta, \zeta). \quad (32)$$

Substituting it in (28), we have

$$\bar{u}_k(x_1, \eta, \zeta) = \frac{\bar{p}_m(\eta, \zeta) \Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} D_{kn}(-\sqrt{\eta^2 + \alpha_n^2 \zeta^2}, -i\eta, -i\zeta) \exp\left(-x_1 \sqrt{\eta^2 + \alpha_n^2 \zeta^2}\right)$$

Returning to the original, we obtain formulas for calculating the displacements at pre-Rayleigh speeds:

$$u_k(x_1, x_2, z) = \frac{1}{4\pi^2} \iint_{R^2} \bar{u}_k(x_1, \eta, \zeta) \exp(-i(x_2\eta + z\zeta)) d\eta d\zeta$$

To determine the stresses, we use the formula (11), which for the Fourier transforms has the type:

$$\sigma_{kj}(x_1, x_2, z) = \frac{1}{4\pi^2} \int_{R^2} \bar{\Sigma}_{kj}^n(x_1, \eta, \zeta) \bar{p}_n(\eta, \zeta) \exp(-i(x_2\eta + z\zeta)) d\eta d\zeta.$$

At pre-Rayleigh velocities in formulas (31) and (32), all the integrands are continuous and tend exponentially to zero by  $x_1 \rightarrow \infty$ . Therefore, the integrals exist and satisfy the damping conditions at infinity. The asymptotic behavior of displacements at infinity is determined by the asymptotic of the transport load on the surface of the half-space.

#### 6. Construction of Green tensor $\Pi_k^m$ at super-Rayleigh speed ( $c_R < c < c_2$ )

If subsonic speed  $c$  is more than Rayleigh speed  $c_R$  then for constructing the solution we transform contour of integration in the  $\varepsilon$ -vicinity of point  $\zeta_R(\eta)$  by any fixed  $\eta$  by way of moving along the circle of radius  $\varepsilon$  in upper half-plane of complex  $\zeta$  by  $z>0$  and in under half-plane by  $z<0$  to get under sign of integral the waves, which tend to zero by  $|z| \rightarrow \infty$ . If  $\varepsilon \rightarrow 0$ , then, with use the theorem on residue of complex analysis, we get Green tensor in the form:

$$\begin{aligned} & 4\pi^2 \Pi_k^m(x_1, x_2, z) = \\ & = \int_{-\infty}^{\infty} \left\{ \text{V.P.} \int_{-\infty}^{\infty} \sum_{j=1}^3 D_{kn}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, i\eta, i\zeta) \frac{\Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} \exp(-x_1 \sqrt{\eta^2 + \alpha_j^2 \zeta^2} - i\zeta z) d\zeta \right\} e^{-i\eta x_2} d\eta - \\ & - i\pi \operatorname{sgn} z \sum_{\pm} \int_{-\infty}^{\infty} \sum_{j=1}^3 D_{kn} \left( -|\eta| \sqrt{\frac{M_R^2 - M_j^2}{M_R^2 - 1}}, i\eta, i\zeta_R^{\pm} \right) \frac{\Delta_n^m(\eta, \zeta_R^{\pm})}{\Delta(\eta, \zeta_R^{\pm}(\eta))} \exp \left( -x_1 |\eta| \sqrt{\frac{M_R^2 - M_j^2}{M_R^2 - 1}} \right) e^{-i(\eta x_2 + z\zeta_R^{\pm}(\eta))} d\eta \end{aligned} \quad (33)$$

Here to calculate the Value Principle integral we can use the formula:

$$\begin{aligned} & \text{V.P.} \int_{-\infty}^{\infty} D_{kn}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, i\eta, i\zeta) \frac{\Delta_n^m(\eta, \zeta)}{\Delta(\eta, \zeta)} \exp(-x_1 \sqrt{\eta^2 + \alpha_j^2 \zeta^2} - i\zeta z) d\zeta = \\ & = \int_0^{\infty} (\Upsilon_{kn}^m(x_1, z, \eta, \zeta) + \Upsilon(x_1, z, \eta, -\zeta)) \exp(-x_1 \sqrt{\eta^2 + \alpha_j^2 \zeta^2}) d\zeta, \\ & \Upsilon_{kn}^m(x_1, z, \eta, \zeta) = D_{kn}(-\sqrt{\eta^2 + \alpha_j^2 \zeta^2}, i\eta, i\zeta) \frac{\Delta_n^m(\eta, \zeta) e^{-i\zeta z}}{\Delta(\eta, \zeta)} \end{aligned}$$

The last integral doesn't have singularities in Rayleigh's points and can be calculated numerically.

The second summand in formula (33) describes the surface Rayleigh waves, which are generated by transport load when  $c_R < c < c_2$ .

By  $c=c_R$  the stationary solution of this problem doesn't exist.

**Conclusion.** Here presented solutions of boundary value problems are very useful for applications when assessing the impact of road trans on the environment. It allows to determine the stress-strain state of the rock massif, depending on its elastic properties, the type of the acting load and the speed of the vehicle. This is especially true now with the development of high-speed road and rail trans, the speed of which can have a devastating impact on the surrounding areas. The obtained solutions allow us to determine the range of possible speeds of movement, taking into account the strength properties of the rock massif and the road surface, which makes it possible to ensure the safety and reliability of operation of modern vehicles.

**REFERENCES**

- [1] Erzhanov Zh.S., Aytaliev Sh.M., Alexeyeva L.A. Dynamics of tunnels and underground pipelines. – Almaty: “Nauka”.- 1989. 240 p.
- [2] Alekseyeva L.A. Fundamental solutions in an elastic space in the travelling load case// Applied mathematics and mechanics. **1991**. Vol 55. No 5. P. 840-848.
- [3] Alexeyeva L.A., Kayshibaeva G.K. Transport solutions of Lame equations. Shock waves // Computational mathematics and mathematical physics. **2016**. Vol.56. No.7. P. 1343–1354.
- [4] Alekseyeva L.A. Somigliana’s formulae for solving the elastodynamics equations for travelling loads.- Applied mathematics and mechanics. V.58 . No 1. **1994**. P.109-116.
- [5] Alekseyeva L.A. Boundary value problems of elastodynamics under stationary moving forces using boundary integral equation method// Engineering Analysis with Boundary Element. **1998**. Vol 22. No 11. P.327-331.
- [6] Alexeyeva L.A. Singular border integral equations of the BVP of elastodynamics in the case of subsonic running loads //Differential equations. Vol. 46. **2010**. No 4. P.512-519.
- [7] Alexeyeva L.A. Singular Boundary Integral Equations of Boundary Value Problems of the Elasticity Theory under Supersonic Transport Loads//Differential equations. **2017**; Vol. 53. No. 3. P . 317–332.
- [8] Alexeyeva L.A. Dynamics of elastic half-space by the action of running load // Applied mathematics and mechanics. - **2007**. Vol.71. No.4. P.561-569.
- [9] Cole J., Huth J. Stresses produced in a half plane by moving loads//Applied Mechanics. **1958**. V.25. P.433-436.
- [10] Brehovskikh L.M. Waves in multilayered media. Moscow: «Nauka». **1973**. 340 p.
- [11] Nowazky. Theory of elasticity. Moscow: «Mir». **1975**. 872 p.
- [12] Kech V., Teodoresku P. Introduction to the theory of distributions with application in engeneering. Moscow: «Mir». **1978**. 518 c.

**Л.А. Алексеева**

Институт математики и математического моделирования МОН РК

**КРАЕВАЯ ЗАДАЧА ДЛЯ УПРУГОГО ПОЛУПРОСТРАНСТВА  
ПРИ ДОЗВУКОВЫХ СКОРОСТЯХ ДВИЖЕНИЯ ПОВЕРХНОСТНОЙ НАГРУЗКИ**

**Аннотация.** Рассматривается первая краевая задача теории упругости для упругого полупространства при движении по его поверхности транспортной нагрузки со скоростью, меньшей, чем скорость распространения упругих волн. На основе обобщенного преобразования Фурье построен тензор Грина - фундаментальное решение задачи, описывающее динамику массива при движении сосредоточенной силы по его поверхности. На его основе построено аналитическое решение для произвольных распределенных по поверхности транспортных нагрузок, движущихся с дорелеевской и сверхрелеевской скоростью. Показано, что при превышении скорости волны Релея транспортные нагрузки генерируют поверхностные релеевские волны.

Задача является модельной для исследования напряженно-деформированного состояния породного массива в окрестности дорожных сооружений при движущемся транспорте.

**Ключевые слова:** упругое полупространство, транспортная нагрузка, дозвуковая скорость, волны Релея, напряженно-деформированное состояние.

## МАЗМУНЫ

<i>Сарсембаева А.Т., Сарсембай А.Т., Мягмаржас О.</i> 2017 жылғы 10 қыркүйекте тіркелген күн жарқылын статистикалық талдау (ағылшын тілінде).....	5
<i>Сарсембаева А.Т., Сарсембай А.Т., Турлыбекова Г.К., Суттикарн С.</i> 2017 жылдың 10-20 сәуір аралығындағы күн жарқылының бақылауы (ағылшын тілінде).....	9
<i>Валиолда Д.С., Жаугашева С.А., Джансейтов Д.М., Жусупова Н.К.</i> <sup>11</sup> Ве нейтрондық гало ядросын сыртқы өріс әсерін есепке алумен зерттеу (ағылшын тілінде).....	12
<i>Алексеева Л.А.</i> Серпімдің кеңістік үшін беттік жұктеме қозғалысының дыбысқа дейінгі жылдамдығы кезіндегі шеттік есеп (ағылшын тілінде).....	21
<i>Жатканбаев А.А.</i> Қауіпсіз стеганография құрылымы Диниц ен үлкен ағын алгоритміне үшін негізделген (ағылшын тілінде).....	31
<i>Сейтмұратов А.Ж., Мәделханова Э.Ж., Парменова М.Ж., Қанибайқызы Қ.</i> Тұракты ядролы интегро-дифференциалдық теңдеулер (ағылшын тілінде).....	37
<i>Онгарбаева Д., Смагулова Л.А., Нұрмұханбетов С.М., Исаева Г.Б.</i> MySQL деректер корын басқару мен оны қолданып клиент-серверлік акпараттық жүйені өңдеу этаптары (ағылшын тілінде).....	46
<i>Сейтмұратов А., Медеубаев Н., Ешмұрат Г., Күдебаева Г.</i> Қозғалмалы жұктеменің әсерінен пайда болатын, серпімді қабаттың төбеліс есебінің жыныш шешімі (ағылшын тілінде).....	54
<i>Тәменов А.М., Жұнісбекова А.С.</i> Геометриялық оптика құбылыстарының математикалық байланыстар алгоритмін Flash-CC, Java script-, бағдарлау орталарында интербелсенді виртуалдау (ағылшын тілінде).....	61
<i>Төленов К.С., Дауітбек Д.</i> Коммутативті емес $H_E(A, \ell_\infty)$ кеңістігінің толықтығы (ағылшын тілінде).....	66
* * *	
<i>Валиолда Д.С., Жаугашева С.А., Джансейтов Д.М., Жусупова Н.К.</i> <sup>11</sup> Ве нейтрондық гало ядросын сыртқы өріс әсерін есепке алумен зерттеу (орыс тілінде).....	75

## **СОДЕРЖАНИЕ**

<i>Сарсембаева А.Т., Сарсембай А.Т., Мягмаржас О.</i> Статистический анализ солнечных вспышек, зарегистрированных 10 сентября 2017 года (на английском языке).....	5
<i>Сарсембаева А.Т., Сарсембай А.Т., Турлыбекова Г.К., Суттикарн С.</i> Мониторинг солнечных вспышек в период 10-20 апреля 2017 года (на английском языке).....	9
<i>Валиолда Д.С., Жаугашева С.А., Джансейтов Д.М., Жусупова Н.К.</i> Изучение нейтронного гало ядра $^{11}\text{Be}$ с учетом влияния внешнего поля (на английском языке).....	12
<i>Алексеева Л.А.</i> Краевая задача для упругого полупространства при дозвуковых скоростях движения поверхностной нагрузки (на английском языке).....	21
<i>Жатқанбаев А.А.</i> Использование алгоритмов Флойда Уоршелла, Беллмана-Форда для добавления перестановок шума блочных шифров для усиления криптостойкости (на английском языке).....	31
<i>Сейтмуратов А.Ж., Маделханова А.Ж., Канибайкызы К.</i> Интегро-дифференциальные уравнения с регулярными ядрами (на английском языке).....	37
<i>Онгарбаева А.Д., Смагулова Л.А., Нурмуханбетов С.М., Исаева Г.Б.</i> Управление базами данных MySQL и этапы разработки клиент-серверной информационной системы с использованием MySQL (на английском языке).....	46
<i>Сейтмуратов А., Медеубаев Н., Ешмурат Г., Кудебаева Г.</i> Приближенное решение задачи о колебании упругого слоя, подвергающегося воздействию подвижной нагрузки (на английском языке).....	54
<i>Татенов А.М., Жұнисбекова А.С.</i> Интерактивная виртуализация в среде Flash-CC, Java script- алгоритмов математических связей явления геометрической оптики (на английском языке).....	61
<i>Туленов К.С., Дауитбек Д.</i> Полнота некоммутативного пространство $H_E(A, \ell_\infty)$ (на английском языке).....	66
<hr/> <i>* * *</i> <hr/>	
<i>Валиолда Д.С., Жаугашева С.А., Джансейтов Д.М., Жусупова Н.К.</i> Изучение нейтронного гало ядра $^{11}\text{Be}$ с учетом влияния внешнего поля (на русском языке).....	75

## CONTENTS

<i>Sarsembayeva A.T., Sarsembay A.T., Myagmarjav O.</i> statistical analysis of x-ray solar flare registered on september 10, 2017 (in English).....	5
<i>Sarsembayeva A.T., Sarsembay A.T., Turlybekova G.K., Sutikarn S.</i> Solar activity monitoring for the period april 10-20, 2017 (in English).....	9
<i>Valiolda D.S., Zhaugasheva S.A., Janseitov D.M., Zhussupova N.K.</i> The study of the neutron halo of the $^{11}\text{Be}$ nucleus taking into account the influence of an external field (in English).....	12
<i>Alexeyeva L.A.</i> Boundary value problem for elastic half-space by subsonic velocities of surface transport loads moving (in English).....	21
<i>Zhatkanbayev A.A.</i> Appliance of floyd warshall, bellman-ford algorithms for adding noise permutations of block ciphers for cryptographic endurance enhancement (in English).....	31
<i>Seitmuratov A.Zh., Madelkhanova A.Zh., Parmenova M.Zh., Kanibaikyzy K.</i> Integro-differential equations with regular kernels (in English).....	37
<i>Ongarbayeva A., Smagulova L., Nurmukhanbetov S., Issayeva G.</i> Managing the MYSQL database and the stages of development of client server information system using MYSQL (in English) .....	46
<i>Seitmuratov A., Medeubaev N., Yesmurat G., Kudebayeva G.</i> Approximate solution of the an elastic layer vibration task being exposed of moving load (in English) .....	54
<i>Tatenov A.M., Zhunisbekova A.S.</i> Interactive virtualization in the environment of Flash-CC, Java script of algorithms of mathematical communications the phenomenon of geometrical optics (in English) .....	61
<i>Tulenov K.S., Dauibek D.</i> The completeness of the noncommutative $H_E(A, \ell_\infty)$ space (in English) .....	66
* * *	
<i>Valiolda D.S., Zhaugasheva S.A., Janseitov D.M., Zhussupova N.K.</i> The study of the neutron halo of the $^{11}\text{Be}$ nucleus taking into account the influence of an external field (in Russian).....	75

**Publication Ethics and Publication Malpractice  
in the journals of the National Academy of Sciences of the Republic of Kazakhstan**

For information on Ethics in publishing and Ethical guidelines for journal publication see <http://www.elsevier.com/publishingethics> and <http://www.elsevier.com/journal-authors/ethics>.

Submission of an article to the National Academy of Sciences of the Republic of Kazakhstan implies that the described work has not been published previously (except in the form of an abstract or as part of a published lecture or academic thesis or as an electronic preprint, see <http://www.elsevier.com/postingpolicy>), that it is not under consideration for publication elsewhere, that its publication is approved by all authors and tacitly or explicitly by the responsible authorities where the work was carried out, and that, if accepted, it will not be published elsewhere in the same form, in English or in any other language, including electronically without the written consent of the copyright-holder. In particular, translations into English of papers already published in another language are not accepted.

No other forms of scientific misconduct are allowed, such as plagiarism, falsification, fraudulent data, incorrect interpretation of other works, incorrect citations, etc. The National Academy of Sciences of the Republic of Kazakhstan follows the Code of Conduct of the Committee on Publication Ethics (COPE), and follows the COPE Flowcharts for Resolving Cases of Suspected Misconduct ([http://publicationethics.org/files/u2/New\\_Code.pdf](http://publicationethics.org/files/u2/New_Code.pdf)). To verify originality, your article may be checked by the Cross Check originality detection service <http://www.elsevier.com/editors/plagdetect>.

The authors are obliged to participate in peer review process and be ready to provide corrections, clarifications, retractions and apologies when needed. All authors of a paper should have significantly contributed to the research.

The reviewers should provide objective judgments and should point out relevant published works which are not yet cited. Reviewed articles should be treated confidentially. The reviewers will be chosen in such a way that there is no conflict of interests with respect to the research, the authors and/or the research funders.

The editors have complete responsibility and authority to reject or accept a paper, and they will only accept a paper when reasonably certain. They will preserve anonymity of reviewers and promote publication of corrections, clarifications, retractions and apologies when needed. The acceptance of a paper automatically implies the copyright transfer to the National Academy of Sciences of the Republic of Kazakhstan.

The Editorial Board of the National Academy of Sciences of the Republic of Kazakhstan will monitor and safeguard publishing ethics.

Правила оформления статьи для публикации в журнале смотреть на сайтах:

www:nauka-nanrk.kz

http://www.physics-mathematics.kz

**ISSN 2518-1726 (Online), ISSN 1991-346X (Print)**

Редакторы М. С. Ахметова, Т.А. Апендиев, Д.С. Аленов  
Верстка на компьютере А.М. Кульгинбаевой

Подписано в печать 05.04.2018.  
Формат 60x881/8. Бумага офсетная. Печать – ризограф.  
5,6 п.л. Тираж 300. Заказ 2.

---

Национальная академия наук РК  
050010, Алматы, ул. Шевченко, 28, т. 272-13-18, 272-13-19